

CAPITOLATO TECNICO PER IMPLEMENTAZIONE SUBRACKs				
Item	Q.TA'	Descrizione	Codice nVent/SCHROFF	
1	6	Front handle, one-piece, width 12.2 mm, clear anodised - 6U	10501-008	
2	5	19" fan unit, 3 fans, 1 U, 230VAC	10713-100	
3	5	19" fan unit, 6 fans, 1 U, 230VAC	10713-104	
4	3	PSU 19" AC/DC Switchmode, Maxpower 100 W, Single, MAX 105, 5V, 16A	13100-102	
5	10	19" AC/DC switch-mode PSUs, maxpower 150 W, single – 5V - 30A - MAX 180-105	13100-150	
6	5	Linear Power Supply – 5V – 1,5A – 8W – PSK 105	13105-001	
7	3	Linear Power Supply – 5V – 4A – PSM 105	13105-006	
8	2	Linear Power Supply – 5V – 6A – PSG 105	13105-011	
9	20	Velcro tape, PE/PA, black, length 300 mm - Conf. 10pz.	20118-624	
10	10	19" front panel with cable eyes, Front panel, AL 7035	20118-761	
11	4	Euroboard mounting kit for EN 60603 connector	20860-115	
12	4	Euroboard mounting kit for EN 60603 connector	20860-116	
13	11	Subrack 1U – Prof. 340mm	20860-203	
14	31	Front handles - 1U - conf. 2pz.	20860-256	
15	3	Front handles - 3U - conf. 2pz.	20860-258	
16	10	Subrack 1U – Prof 280mm per flussi aria – Basic Kit	20860-602	
17	4	Subrack 1U – Prof 220mm per flussi aria – Basic Kit	20860-621	
18	2	MultipacPRO 19" Chassis, Aluminum, Perforated Top and Base, 4 U, 460 mm	20860-634	
19	3	PSU Front Panel for Maxpower 100, Single	21006-943	
20	1	Grub screw (M2.5x8), steel nickel plated - conf. 100pz	21100-276	
21	10	Fibre optic cable ducting (Conf. 4pz.)	23130-391	
22	1	Countersunk screw, torx (M4x14), steel zinc plated - conf. 100pz.	24560-130	
23	6	Guide rails, plastic, standard, 220mm deep - 2mm groove- conf. 10pz.	24560-353	
24	3	Subrack 3U - EuropacPRO kit, flexible design, shielded, for backplane mounting – Prof. 295mm	24563-143	
25	2	Subrack 6U – Prof. 355mm – Shielded	24563-444	
26	10	Cable Channel, Horizontal, 1 U	24630-058	
27	5	Front panel, front anodized, unshielded, screw assembly - 3U - 10HP - conf. 5pz.- (Filling)	30818-279	
28	5	Front panel, front anodized, unshielded, screw assembly - 3U - 12HP - conf. 5pz.- (Filling)	30818-281	
29	5	Front panel, front anodized, unshielded, screw assembly - 3U - 14HP - conf. 5pz.- (Filling)	30818-282	
30	5	Front panel, front anodized, unshielded, screw assembly - 3U - 16HP - conf. 5pz.- (Filling)	30818-284	
31	5	Front panel, front anodized, unshielded, screw assembly - 3U - 28HP - conf. 5pz.- (Filling)	30818-296	
32	6	Front panel, front anodized, unshielded, screw assembly - 3U - 42HP - (Filling)	30818-310	
33	5	Front panel, front anodized, unshielded, screw assembly - 3U - 4HP - conf. 5pz.	30838-043	
34	5	Front panel, front anodized, unshielded, screw assembly - 6U - 4HP - conf. 5pz.	30838-124	
35	5	Front panel, front anodized, unshielded, screw assembly - 6U - 5HP - conf. 5pz.	30838-125	
36	8	Cover plates - Prof. 220mm	30860-501	
37	20	Cover plates - Prof. 280mm	30860-502	
38	18	Cover Plates – Prof 340mm - conf. 1pz.	30860-503	
39	6	Cover Plates – Prof. 340mm	30860-521	
40	10	Front panel – 8HP	31006-677	
41	1	Horizontal rail, AL-Profile, anodised, Type L-KD light, short lip - conf. 10pz.	34560-184	
42	1	Horizontal rail, Al-Profile, anodised, Type L-ST light, standard - conf. 10pz.	34560-484	
43	1	Horizontal Rail, Rear, Type H-ST, Heavy, Standard, 84 HP	34560-584	
44	2	Threaded insert, St, zinc-plated, height 5 mm, depth 2 mm, M 2.5 thread - 84HP - conf. 10pz.	34561-384	
45	60	Guide rails for plug-in units and modules - 160mm - conf. 10pz.	34564-891	
46	60	Guide rails for plug-in units and modules - 220mm - conf. 10pz.	34564-892	
47	10	Cable Eye, Plastic, 30W 100D	60118-459	
48	10	Double steel cable eye - conf. 5pz.	60118-473	
49	10	Rubber pad for double steel cable eye - conf. 5pz	60118-475	
50	10	Cable ducting to engage	60239-021	
51	20	Barre di alimentazione - Solder strip conductor	60800-064	
52	25	EN 60603 (DIN 41612) Connector, Type H	69001-733	