



Lista materiali

n. 2 HEIDENHAIN RCN 8511 (1244751-01)

Absolute angle encoder (singleturn) with integral bearing and integrated stator coupling
System accuracy: $\pm 1.0''$
Data interface: EnDat22
Positions per revolution: 536870912
Power supply: 3.6 V ... 14 V
Shaft: Hollow shaft, diameter 60 mm
Degree of protection: IP 64 (EN 60529)
Operating temperature: 0/+50 °C
Electrical connection: Flange socket Ultra-Lock, male, 12-pin
Pin configuration: D680849
Safety concept: For applications up to SIL 2 as per EN 61508 and PL d as per EN ISO 13849.

n. 4 HEIDENHAIN 643450-01

Adapter cable for different connector connection
Cable type: PUR \varnothing 6.0 mm
Cable design: 6x2x0.19 mm²
Cable length: 1.00 m
Encoder side: Connector ultra-lock, female 12-pin
Side of subsequent electronic: Coupling M23, male, 17-pin

n. 1 LEINE-LINDE HEIDENHAIN HROBUSTGATEAY (1125078-01)

Robust DIN-rail-mounted gateway CRG CANOpen
Power supply: 9 V ... 36 V DC
Input signal: Synchronous serial EnDat 2.1 with incremental signals
Electrical connection 2: Flange socket with coupling ring M23, female, 17-pin
Data interface: CANOpen interface
Electrical connection: Terminal strip 10-pin