

drylin® R press-fit bearings | Product range

Made from iglidur® L100





Order key

Type

Size

W L M-0608-10

igidur® L100	Series L1	Metric	Inner Ø	Outer Ø	Length
--------------	-----------	--------	---------	---------	--------



- Extreme wear resistance
- Low coefficients of friction



⁸⁰⁾ Measured with gage

Please note: installation instructions ► Page 945

Material table ► Page 1435



min. -40 °C

max. +100 °C

Dimensions [mm]

d1	d1-Tolerance ⁸⁰⁾	d2	b1	bs	Part No.
6	+0.000 +0.040	8	10	6	WLM-0608-10
8	+0.000 +0.050	10	12	8	WLM-0810-12
10	+0.000 +0.050	12	14.5	10	WLM-1012-14
10	+0.000 +0.050	12	16	10	WLM-1012-16
12	+0.000 +0.050	14	16	10	WLM-1214-16
12	+0.000 +0.050	14	25	15	WLM-1214-25
16	+0.000 +0.050	18	18	10	WLM-1618-18
16	+0.000 +0.050	18	26	16	WLM-1618-26
20	+0.000 +0.060	23	22.5	12.5	WLM-2023-22
20	+0.000 +0.060	23	30	20	WLM-2023-30
22	+0.000 +0.060	25	30	20	WLM-2225-30
25	+0.000 +0.060	28	29	19	WLM-2528-29
25	+0.000 +0.060	28	35	25	WLM-2528-35
30	+0.000 +0.060	34	34	24	WLM-3034-34
30	+0.000 +0.060	34	40	30	WLM-3034-40
40	+0.000 +0.060	44	40	30	WLM-4044-40
40	+0.000 +0.060	44	50	40	WLM-4044-50
50	+0.000 +0.070	55	50	40	WLM-5055-50
50	+0.000 +0.070	55	60	50	WLM-5055-60